

# Labtex

## AATCC Washing Machine For Home Laundering Test

Model: **LBT-M6**



<b>Washing Cycle</b>	1 For AATCC LP1 - Normal - Permanent Press, - Delicate 2 Drain & Spin 3 Rinse & Spin 4 Customized*
<b>Water Control</b>	25°C~60°C±1°C (wash) Tap water (Rinse)
<b>Washing Load</b>	10.5KG
<b>Power</b>	220V/50Hz/1KW OR 120V/60Hz/1.5KW
<b>Packing Size</b>	700mm x 680mm x 1040mm
<b>Packing Weight</b>	78KG

**OPTIONAL:**  
LBT-Portable  
Handheld programmer

Meet Standard

**AATCC LP1, 88B, 88C, 124,  
130, 135, 142, 143, 150, 159,  
172, 179**

\* Base on customer needs to tailor made the specific washing sequence with LBT-Portable Handheld Programmer.

### Washing Cycle for AATCC LP1-2018

Cycle (Table I)	Normal	Permanent Press	Delicate
Water Level Medium	19±1gal	19±1gal	19±1gal
Agitation Speed	86±2spm	86±2spm	27±2spm
Washing Time	16±1min	12±1min	8.5±1min
Final Spin Speed	660±15rpm	500±15rpm	500±15rpm
Final Spin Time	5±1min	5±1min	5±1min

### Water Temperature Control

Wash	Rinse
From 25°C to 60°C±1°C. Setting Washing Temperature in 27°C, 41°C 49°C, 60°C for AATCC Standard, <b>or</b> any other temperature will be specified.	<b>Tap Water</b>